

Pneumatic clipper

KN-4S KE



The KN-4S KE clipper is designed for single clipping of various fillers (minced meat, butter and other food pastes) in polyamide, cellulose and collagen bags and tubular casings. If necessary, a twine loop is manually fed under the clip for hanging sticks. The excess casing at the end of the stick is cut using a cut-off knife. The clipper is operated by a single qualified operator.

Technical specifications

Model	KN-4S KE
Clipping cycle, max, s	2 - 3
Casing caliber, mm	40 - 120
Type of clips	E
Cut-off knife	active
Clip clamp drive	pneumatic
Clipping drive	pneumatic
Loop feed	manual
Version	floor standing
Bags width, max, mm	450
Bags thickness, max, μm	60
Air pressure in the working pneumatic network, Mpa	0.5 - 0.6
Air consumption, max, L/cycle	1.2
Dimensions, mm:	
Length* Width* Height	800*820*1900
Net weight, kg	45

* The clipper can be made to fit other types of clips

Advantages:

- Available cut-off blade to remove excess casing or bag;
- The knife drive switching-off;
- The bag harness for clip application is made by the pneumatic cylinder;
- Clip application pneumatic drive;
- For clipping using A type clips of various fillings in polyamide, cellulose, collagen bags and casings;
- Full clipping cycle (clipping and cutting) from 2 to 3 sec;
- Working pressure from 5 to 6 MPa (kg/cm²).

