



NATURAL CASING THREADING DEVICE

Natural casing threading device NO-1 is designed to accelerate and simplify the process of casing threading on the filler cog or twisting device KOMPO during production of boiled, cooked smoked, semismoked, dry, liver, blood sausages and small sausages. Reduces the worker's hands contact time with a wet, cold casing. Reduces physical stress when the casing is thread by the maker.



- wide range of casing to be threaded;
- adjustable rotation frequency of the roller which allows to use casings of improper quality;
- automatic switching-on of the device when tilted to the spindle;
- unitizing with KOMPO portioning machines and fillers;
- possibility to install the device on molding table (on a special stand);
- quick-detachable threading roller; high mobility of the device due to integrated power supply unit;
- power supply voltage 220V, 50Hz;
- additional sponge roller for delicate casing in a set;
- high level of moisture protection;
- patent application is filed.



Technikal specifications:

Model	NO-1
Range of casing calibers to be threaded, mm	13-44
Range of spindle diameters, mm	10-30
Casing threading speed, m/s	1,5-3,4
Nominal power of electric motor, max., kW	0,2
Power supply, V	220
Parameters of electric mains	1/N/РЕ АС 230В 50 Гц
Overall dimensions, mm, maximum, without fastenings:	
Length*Width*Height	550*250*250
Netweight, kg	8,5
Overall dimensions, mm, maximum, with bracket for fastening	
to KOMPO portioning machines (in initial position):	
Length*Width*Height	500*500*500
Netweight, kg	13,0
Overall dimensions, mm, maximum, with bracket for installation	
on the table (in upper most initial position):	
Length*Width*Height	550*500*600
Netweight, kg	15,0

LLC "Machine-building enterprise "KOMPO"

Republic of Belarus 224032 Brest, st. Y. Kupaly, 108 D www.kompo.by e-mail: kompo@kompo.by







+375 33 911-30-30



компо



kompo_by



kompoequipment